

MODEL EV-300 WASTEWATER EVAPORATOR



Cut Down
On Disposal
Costs
By
Evaporating
Your
Unwanted
Wastewater

FEATURES:

- Stainless Steel Insulated Lids
- Circulation Motor
- Thermostat Control
- Low Water Shut Off Switch
- Gas Fired
- Draft Inducer
- Fully Insulated
- Dual Sludge Collection Tanks
- Sludge Scraper
- Will Evaporate Up To 13 Gallons per Hour

CUSTOM SIZES AVAILABLE



800-251-0018
www.axeequipment.com

Not for use with Flammable Liquids

AXE Equipment reserves the right to change its prices and product specifications without notice.

EV300 SPECIFICATIONS

Floor Space Required	44"W x 98"L x 84"H
Inside Tank Dimensions	36"W x 72"L x 32"H
Loading Height	45 ¼"
Solution Depth	27"
Solution Capacity	300 Gallons
Tank Construction	12 Gauge
Insulation	1" Fiberglass with R Rating of 3.9
Pipe Plug	(2) 1 ½"
Steam Vent	6"
Gas Vent	4"
Shipping Weight	1200 lbs
MOTOR SPECIFICATIONS	
Circulation Motor	1/10 HP-12 RPM 2.6 Amps 115V 1 Phase
Draft Inducer	1550 RPM 115V 1 Phase 1.0 Amps
Gas Heater	115V 1 Phase 3.0 Amps 225,000 BTU .272 Gas Orifice

AXE Equipment reserves the right to change its prices and product specifications without notice.



For Quality & Efficiency Look to AXE

Highway 177 North/ P.O. Box 296/ Council Grove, KS 66846

800-251-0018/ Fax 620-767-5482

www.axeequipment.com Email: info@axeequipment.com